

HOOKLOADERS

WHERE EXCELLENCE COMES AS STANDARD



HYVA[®] LIFT

www.hyva.com

HYVA LIFT HOOKLOADERS WHERE EXCELLENCE COMES AS STANDARD



Range

The extensive and unbeatable range of Hyva Lift hookloaders extends from 1 to 40 tons to satisfy any requirement. Constructed from high yield steels the design provides for height and weight advantages which maximise the stability and payload.

Systems in the 3 to 5 tons range are fitted with a knuckle arm while systems in the 6 to 40 tons range are fitted with a sliding arm. Sliding arm systems with an elbow like construction (SK) can be delivered in the range of 20, 22, 26 and 30 tons capacity.

Various options are available including draw bar applications and hook/skip or hook/crane combinations. The Hyva Lift hookloader can be adapted to suit any application.

GVW (ton)	lifting capacity (ton)	System length (mm)*	System weight (kg ±)	Container-length (mm)	Hyva Lift Type
3,5	1	1800	220	1800-2300	R
4 to 7,5	3	2300-3200	405-580	2500-3750	K
4 to 7,5	4	3300-3900	760-790	2800-4900	S
7,5 to 10	5	3400-4000	580-640	3990	K
8 to 12	6	3300-4500	920-1020	2800-5500	S
10 to 14	8	3300-4500	1080-1225	2800-5500	S
12 to 16	10	3900-5700	1750-2150	3150-6800	S
12 to 16	12	3900-5700	1750-2150	3150-6800	S
16 to 20	14	3900-5700	1750-2150	3150-6800	S
18 to 26	16	3900-5700	1750-2150	3150-6800	S/K
18 to 26	18	3900-5700	1750-2150	3150-6800	S/K
26 to 32	20	4500-6700	2250-3100	3050-7600	S/SK ¹ /K
26 to 35	22	4500-6700	2300-3200	3050-7600	S/SK ¹
30 to 37	26	4500-6700	2425-3200	3050-7600	S/SK ¹
35 to 40	30	5300-6700	3000-3450	4400-7600	S/SK
40 to 45	35	5800-6700	3300-3525	4650-7800	S
45 to 50	40	6500-7100	3850-4200	5000-8200	S

*) Available lengths:
2300/2800/3200/3300/3600/3900/4200/4500/4700/4900/5100/5350/5550/5700/5800/6000/6200/6500/6700/6900/7100/7300/7500

1) SK Type available in lengths from 4900

Where excellence comes as standard

The unbeatable range of hookloaders gives you flexibility, strength and proven reliability. Hyva Lift hookloaders are manufactured to the highest standards for waste, construction and municipal applications throughout the world.

All Hyva Lift products are distributed through a worldwide network of independent dealers or subsidiaries of the Hyva Group. This network keeps Hyva Lift up to date with all developments in the market and provides an excellent after sales service.



For easy sliding of the arm of the hook mast, Ertalon sliding blocks are used.



The pick-up hook is standard provided with a counter balance weight and is made out of high quality steel. All hooks are easily detachable.



Standard in-cab pneumatic controls for all functions.



The pivoting point at the rear of the system is located as low as possible into the bottom frame.



The Hyva Lift hookloaders are delivered with container supporting rolls for quiet and easy loading of the containers. Two rear rollers, which support the container's lower frame, have bronze bearings.



A mechanical main arm locking, for safer tipping of the containers.

Dealer: